


Strength in Technology

# **FortisBIO**<sup>™</sup> **Peptide & Protein** Columns INCLUDES 1.74 FORTISBIO UHPLC COLUMNS

**HPLC/UHPLC** Columns

FortisBIO<sup>®</sup> C18 and C4 are stationary phases with optimised pore size to allow the efficient and robust separation of Biomolecules.

1.7µmFortisBIO<sup>®</sup> phases allow ultra high performance separation of proteins and peptides.



- 300Å Pore size optimised for Peptides and Proteins • 1.7µm UHPLC particle size - increases sensitivity options • Sharp Efficient peak shapes Excellent for Peptide mapping

Large Pore optimum for Peptides

Choose from C18 or C4 ligands

**1.7µm Particle for Bio UHPLC** 


5µm Particle for Analytical scaling

# FortisBIO<sup>®</sup> C4

- 300Å Pore size optimised for Peptides and Proteins
- 1.7µm UHPLC particle size increases sensitivity options
- Stable, robust ligand density, low bleed.
- Analyse large hydrophobic molecules

Biomolecules are a diverse range of compounds, amino acids, proteins, peptides, nucleic acids, vitamins and obtaining quality separations is paramount. FortisBIO<sup>™</sup> C4 and C18 are 300Å optimised stationary phases providing improved selectivity, throughput, sensitivity and column robustness for biomolecules. Choose C18 for more hydrophilic proteins and C4 for more hydrophobic molecules.

Choose particle size based upon your LC system and the sensitivity of analysis that you require.









5u Vvdac° C18

150x2.1mm

1.7um FortisBIO C18

100x2.1mm

# FortisBIO<sup>®</sup> C18

FortisBIO<sup>°</sup> C18 is a 300Å material specifically optimised for the retention and resolution of peptides and proteins. Based upon our traditional silica and bonded technology, sharp peak shapes, excellent analyte recovery and high sensitivity can all be achieved whether in analytical scale or in UHPLC scale. Improvements in sensitivity and resolution of peptides, proteins, tryptic digests can all be gained with the minimum of effort

- 300Å Pore size optimised for Peptides and Proteins
- 1.7µm UHPLC particle size increases sensitivity options
- Sharp efficient peak shapes
- Fully scaleable 1.7µm 5µm particle sizes for method transfer

#### 1.7µm FortisBIO C18 - INCREASE SENSITIVITY

433332

XIII -

3000 3000

2000 -

10000

5000 4500 4000

XIIII XIIII XIIII XIIII

2008

15000

5008

FortisBIO<sup>™</sup> C18 is available as 1.7µm particle size for use in UHPLC, this means that sensitivity of methods and resolution of complex mixtures such as tryptic digests and closely related peptides can be improved:

#### - Sharp Peaks

 $1.7\mu$ m FortisBIO's sharp peak shapes provide a high level of resolution between compounds. Efficiency of this small particle and its ability to work at high pressure means that methods can now be developed with more speed.

#### - Increase Sensitivity

If you use a small 1.7 $\mu m$  particle then sensitivity of low abundance peptides will be enhanced.



FortisBIO 300Å material is available as  $1.7\mu$ m for use in UHPLC or as  $5\mu$ m for use in analytical LC. A pure silica porous particle and optimum bonding chemistry leads to fully scaleable methods, reducing the time spent in method development and QC/QA transfer.


#### - Improved Scaling

FortisBIO C18 provides the same selectivity whichever particle size is chosen.

However in the region of 50% gain in peak sensitivity can be achieved by moving to UHPLC.

- FortisBIO C18 50x2.1mm 1.7µm

- FortisBIO C18 50x2.1mm 5µm
- 1. GLY-TYR (238.2MW) 2. VAL-TYR-VAL (379.5 MW) 3. MET-Enkephalin (573.7) 4. LEU-Enkephalin (555.6 MW) 5. Angiotensin II (1046.2 MW)



mandant niteritari

#### FortisBIO C18 - PEPTIDES

The excellent surface coverage of the C18 ligand on the FortisBIO 300Å material gives multiple benefits for peptide analysis:

#### - Improved Peak Shape


FortisBIO C18 is built around the same bonding technology as our existing small molecule C18 hence superior peak shapes are achieved.

#### - Improved Sensitivity

If you can improve peak shape then you will improve both resolution and sensitivity of the method.

1. GLY-TYR (238.2MW) 2. VAL-TYR-VAL (379.5 MW) 3. MET-Enkephalin (573.7) 4. LEU-Enkephalin (555.6 MW) 5. Angiotensin II (1046.2 MW)

 $\begin{array}{l} \mbox{Columns: 50x2.1mm 5} \mbox{$\mu$} \\ \mbox{A: 0.1\% TFA} \\ \mbox{B: 0.1\% TFA in ACN} \\ \mbox{10-40\% B in 10min} \\ \mbox{$\lambda$ - 220nm} \end{array}$ 



#### FortisBIO C18 - PROTEINS

The excellent surface coverage of the C18 ligand on the FortisBIO 300Å material gives multiple benefits for protein analysis:

#### - Improved Recovery

FortisBIO C18 provides sharp peak shapes due to the surface coverage, this provides increased recovery of protein samples.

#### - Improved Reproducibility


By having a controlled surface coverage reproducibility of the analysis is improved from sample to sample.

#### 1. Ribonuclease A

- 2. Cytochrome C
- 3. Halo-Transferrin

4. Apomyoglobin

Columns:  $50x2.1mm 5\mu$ A: 0.1% Formic acid B: 0.1% Formic acid in ACN 10-60% B in 15min  $\lambda$  - 220nm



## Improve Recovery


#### FortisBIO C18 - CASEIN COMPARISON

Recovery of proteins is of paramount importance to the analyst, FortisBIO C18 ensures good peak shape, resolution and recovery of complex protein and peptide samples.

If recovery of low abundance proteins is reduced then sensitivity will be degraded for these proteins.

5µm FortisBIO C18 50x2.1mm

A: 0.1% Formic acid in Water B: 0.1% Formic acid in ACN 10-60% Gradient in 15mins 214nm




#### FortisBIO C18 - BASIC PEAK SHAPES

Peak Shapes are of great significance in analysis of biomolecules since both resolution of structurally similar compounds and also sensitivity of molecules will be heavily effected.

FortisBIO C18 and C4 are both manufactured to ensure that surface coverage is high, therefore reducing any secondary negative interactions which could compromise peaks shapes.

Small basic probes prove whether there are any secondary silanol interactions which would compromise peak shapes.

| Basic Compound       | Asymmetry<br>Competitor | Asymmetry<br>FortisBIO C18 |
|----------------------|-------------------------|----------------------------|
| 4-Ethylaniline       | 1.58                    | 1.30                       |
| N,N- Dimethylaniline | 1.52                    | 1.28                       |



# Reproducibility

#### REPRODUCIBILITY

The excellent surface coverage of the C18 ligand on the FortisBIO 300Å material gives multiple benefits for peptide analysis: - Improved Reproducibility FortisBIO C18 is built around the same bonding technology as our existing small molecule C18 (100Å ) hence reproducibility is assured. A most important variable - Different Batches Multiple batches show reproducible results 1. GLY-TYR (238.2MW) 2. VAL-TYR-VAL (379.5 MW) 3. MET-Enkephalin (555.6 MW) 5. Angiotensin II (1046.2 MW)

#### REPRODUCIBILITY


The excellent surface coverage of the C18 ligand on the FortisBIO 300Å material gives multiple benefits for protein analysis:

#### - Improved Recovery

FortisBIO C18 provides sharp peak shapes due to the surface coverage ligand, this provides increased recovery of protein samples.

#### - Improved Reproducibility By having a controlled surface coverage reproducibility of the analysis is improved from sample to sample.

Probe 1Probe 2



# FortisBIO<sup>®</sup> C4

FortisBIO<sup>®</sup> C4 is a 300Å material specifically optimised for the retention and resolution of large peptides and proteins. Sharp peak shapes, excellent analyte recovery and high sensitivity can all be achieved whether in analytical scale or in UHPLC scale. The C4 ligand provides a high density bonding, resulting in a chemically stable, robust, low bleed phase.

- 300Å Pore size optimised for Peptides and Proteins
- 1.7µm UHPLC particle size increases sensitivity options
- Sharp efficient peak shapes
- Fully Scaleable 1.7µm 5µm particle sizes for method transfer




#### FortisBIO C4 - C4 STABILITY IN ACIDIC CONDITIONS

The excellent surface coverage of the C4 ligand on the FortisBIO 300Å material gives multiple benefits for peptide and protein analysis:


#### - Improved Lifetime

- Improved Peak Shapes

FortisBIO C4 has an improved lifetime over other C4 columns. The bonding process is optimised to increase the surface coverage and remove secondary interactions



#### FortisBIO C4 - ANGIOTENSIN I



# **BIO** Considerations


- 300Å large pore size for Peptides and Proteins
- Reproducible bonding
- Sharp efficient peak shapes for peptide mapping
- UHPLC correct fittings

#### PORE SIZE - 100Å vs 300Å

The importance of pore size is critical in the separation of large peptides and proteins. In 'normal' analytical small molecule work a 100Å silica template is typically used, however this can lead to poor resolution, sensitivity and recovery of biomolecules.

More common therefore for biomolecule work of analytes >2 KDa would be the use of a 300Å silica particle.

Even with this wider pore size Fortis 1.7µm columns will still operate at the higher pressures required by UHPLC systems.



#### **CORRECT FITTING OF UHPLC COLUMNS**


<del>۳</del>...

UHPLC column fitting is of crucial importance. since the addition of the smallest "dead" or void volume to these new low volume UHPLC systems will severely impact upon the performance of the column. Even the smallest 1mm void produced from fitting the column can lead to a sharp decrease in efficiency and peak shape from what should be achieved.


#### - Adjustable fittings


Stainless steel fittings have been widely adapted due to the high pressures involved, however if the ferrule is also stainless steel and immovable once in place then this can create a void when switching between different manufacturers columns.

A fully adjustable UHPLC fitting should always be adapted in order to ensure that the fitting of the column is perfect every single time regardless of UHPLC hardware.



#### **DIFFERENT BUFFERS - TFA vs FORMIC ACID**







#### DIFFERENT CONCENTRATION OF BUFFER

TFA is a most common buffer in bioanalysis due to its ion pair effects. When peptide mapping the choice of mobile phase helps reduce or eliminate the charged functionalities of the peptides so they retain on the hydrophobic surface.

because as an acid it protonates carboxyl groups whilst its ability as an ion-pair reagent neutralises positively charged basic functions.

concentration of TFA does not compromise MS detection, as it may cause ion suppression in electrospray MS. Choice of buffer concentration will therefore be a compromise between resolution, peak shapes and sensitivity in UV and MS.





# Applications

#### Fortis H2o - AMINO ACIDS

Amino acids play a fundamental role in bioanalysis.


Having many functions in metabolism critical to life and seen as the building blocks of proteins. Linear chains of amino acids can be formed in many sequences to produce a variety of proteins.

HPLC analysis is made challenging by the diversity of the various analytes involved. A variety of hydrophobicities and functionality, basic, acidic and neutral. The amine and carboxylic functional groups present allow the amino acid to have amphiprotic or zwitterionic properties, either the carboxylic acid or the animo group being charged.

Fortis H2o shows the ability to retain and resolve all of the amino acids essential to humans.

For small molecules such as amino acids a 100Å material such as the Fortis H2o is complimentary to the FortisBIO columns.

#### FortisBIO C18 - INSULIN



# 1.7um Fortis<sup>®</sup> H2o

# **Applications**


#### FortisBIO C18 - HUMAN GROWTH FACTOR


Epidermal Growth Factor is a growth factor that stimulates cell growth, proliferation and differentiation by binding to its receptor EGFR. Human EGF is a 6045Da protein with 53 amino acid residues. FortisBIO C18 ensures good peak shape, resolution and recovery of large complex proteins.

Human Growth Factor (mw = 6045Da)

1.7µm FortisBIO C18 50x2.1mm

A: 0.1% TFA in Water B: 0.1% TFA in ACN 10-50% Gradient in 45mins 214nm





# **BIO** Column Care

- Each FortisBIO<sup>™</sup> column is shipped with its own test certificate
- Please confirm the column performance on your system
- FortisBIO will operate between pH 2-9
- Operate upto 90°C
- 1.7µm is pressure rated to 1000bar

## **Operating Conditions**

FortisBIO<sup>-</sup> columns are stable between pH 2 to 9 and can be used with all common reversed phase mobile phase solvents, Acetonitrile, MeOH, Water as well as common buffers, Formic acid, TFA, Acetic acid, Ammonium acetate. They will operate at elevated temperatures to aid the separation upto 90°C.

NB: Most columns will have a reduced lifetime if operated at extremes of temperature, pressure and pH. Try and avoid excessive use or increased combinations of temperature and pH.

5µ FortisBIO columns will safely operate upto 600bar (8940 psi), whilst 1.7µm FortisBIO UHPLC columns will operate upto 1000bar (15,000psi)

All columns should be installed to minimise dead-volume, this is especially important in UHPLC operating systems. Use a UHPLC fitting designed to handle the increased pressures whilst providing a flexible connection to minimise any extra volume, such as Fortis UHPFIT-2.

### **Column Regeneration**

Cleaning of contaminated columns can be achieved by careful flushing following the procedure below:

- · Column should be flushed free from buffer to start any cleaning procedure. High concentrations of water should be used to do this
- · Column should be flushed in the reverse direction to ensure minimal wash path and also to ensure no blockage of the frits (not all manufacturers columns can do this, please confirm with your manufacturer)
- 20 column volumes should be used for each wash stage
- 95:5 Water : ACN (removal of buffer)
- 100% ACN
- 100% IPA
- 100% ACN
- 50:50 Water : ACN
- Reorientate column in correct flow direction and re-equilibrate into the required mobile phase.

## **Column Storage**

- Columns should be stored in at least 40% organic solvent with no buffers present
- Endfittings should be fitted to ensure no evaporation of solvent and consequent column "dry-out"
- Columns should be stored at room temperature free from vibration
- If a column is to be stored for any period of time, ideally column cleaning should take place as per guidelines

For further technical assistance or applications contact: technicalsupport@fortis-technologies.com

# 1.7µm UHPLC part numbers

| 1.7µm FortisBIO C18 |            | Column Length              |                            |                     |                             |                             |  |  |
|---------------------|------------|----------------------------|----------------------------|---------------------|-----------------------------|-----------------------------|--|--|
|                     |            | 20                         | 30                         | 50                  | 100                         | 150                         |  |  |
|                     | 2.1        | BI0318-020101              | BI0318-020201              | BI0318-020301       | BI0318-020501               | BI0318-020701               |  |  |
| Column Diameter     | 3.0        | -                          | BI0318-030201              | BI0318-030301       | BI0318-030501               | -                           |  |  |
|                     | 4.6        | -                          | BI0318-050201              | BI0318-050301       | BI0318-050501               | -                           |  |  |
|                     |            |                            |                            |                     |                             |                             |  |  |
| 1.7µm FortisBIO C4  |            | Column Longth              |                            |                     |                             |                             |  |  |
|                     |            |                            |                            | Column Length       |                             |                             |  |  |
|                     |            | 20                         | 30                         | Column Length<br>50 | 100                         | 150                         |  |  |
|                     | 2.1        | <b>20</b><br>Bl0304-020101 | <b>30</b><br>BI0304-020201 | Ŭ                   | <b>100</b><br>BI0304-020501 | <b>150</b><br>Bl0304-020701 |  |  |
| Column Diameter     | 2.1<br>3.0 |                            |                            | 50                  |                             |                             |  |  |

## 5µm part numbers

| 5µm FortisBIO C18                   |     | Column Length              |                            |               |               |                             |               |  |
|-------------------------------------|-----|----------------------------|----------------------------|---------------|---------------|-----------------------------|---------------|--|
|                                     |     | 20                         | 30                         | 50            | 100           | 150                         | 250           |  |
|                                     | 2.1 | BI0318-020105              | BI0318-020205              | BI0318-020305 | BI0318-020505 | BI0318-020705               | -             |  |
| Column Diameter                     | 3.0 | -                          | BI0318-030205              | BI0318-030305 | BI0318-030505 | BI0318-030705               | -             |  |
|                                     | 4.6 | -                          | BI0318-050205              | BI0318-050305 | BI0318-050505 | BI0318-050705               | BI0318-050905 |  |
|                                     |     |                            |                            |               |               |                             |               |  |
|                                     |     |                            |                            |               |               |                             |               |  |
| 5µm FortisBIO C4                    |     |                            |                            | Column        | Length        |                             |               |  |
| 5µm FortisBIO C4                    |     | 20                         | 30                         | Column<br>50  | Length        | 150                         | 250           |  |
| 5µm FortisBIO C4                    | 2.1 | <b>20</b><br>BI0304-020105 | <b>30</b><br>BI0304-020205 |               | Ŭ             | <b>150</b><br>BI0304-020705 | 250           |  |
| 5µm FortisBIO C4<br>Column Diameter |     |                            |                            | 50            | 100           |                             | 250<br>-<br>- |  |

# **UHPLC Sample Filter**



- Low volume in-line filter for all UHPLC columns No backpressure increase
- Increase lifetime of UHPLC columns
- Change over time seconds not minutes

## **UHPLC** Fittings



- Perfect fit every time
- No dead volume
- No tools required
- Change over time seconds not minutes

Fortis UHPLC fittings are designed to offer the perfect fit for all UHPLC columns. Quickly change the ferrule depth to adapt to any column. Hand-tight fitting requires no tools. Fitting is ideal for 1.7µm Fortis UHPLC columns as they are manufactured to withstand 20,000psi.

#### www.bgb-shop.com/fortis

Capillary pricing is available upon request

Capillary pricing is available upon request

# **UHPLC In-line Filters** UHPSAV2 UHPLC In-line filter pk 2 UHPSAV4 UHPLC In-line filter pk 4 **UHPLC Fittings**

#### UHPFIT-2 UHPLC Fitting pk 2 UHPFIT-4 UHPLC Fitting pk 4

# WORLDWIDE AVAILABILITY





45 Coalbrookdale Road Clayhill Industrial Park Neston Cheshire, UK CH64 3UG t: +44 151 336 2266 f: +44 151 336 2669 www.fortis-technologies.com e: info@fortis-technologies.com

Company No. 5449466 VAT No. 866 8966 43 Fortis products are available worldwide. For the distributor in your country, contact Fortis international Sales Office, UK by telephone, fax or email: info@fortis-technologies.com

- Austria
- Bangladesh
- Brazil
- Canada
- China
- Columbia
- Czech Republic
- Ecuador
- Egypt
- France
- Germany
- Greece
- Holland

- Hong Kong
- HungaryIndia
- Ireland
- Israel
- Italy
- Japan
- Sapan
   Korea
- Norea
  Malaysia
- Malaysia
   Mexico
- Netherlands
- Norway
- Puerto Rico

- PolandPortugal
- Romania Russia
- Singapore
- South Africa
- Spain
- Sweden
- Switzerland
- Taiwan
- Thailand
  - Turkey
  - USA

For technical support or applications contact : technicalsupport@fortis-technologies.com

# For more information VISIT : www.bgb-shop.com/fortis



www.bgb-shop.com

 Switzerland
 BGB Analytik AG • Rohrmattstrasse 4 • 4461 Böckten • Phone +41 61 991 00 46 • Fax +41 61 991 00 25 • sales@bgb-analytik.com

 BGB Analytik SA • Route de Pré-Bois 20 • 1215 Genève 15 • Phone +41 22 788 49 43 • Fax +41 22 788 49 45 • sales.fr@bgb-analytik.com

 Benelux
 BGB Analytik Benelux B.V. • Drielandendreef 42-44 • 3845 CA Harderwijk • Phone +31 341 700270 • Fax +31 341 700271 • sales.benelux@bgb-analytik.com

 France
 BGB Analytik France S.A.S. • 81 Vie de l'Etraz • 01630 St. Jean de Gonville • Phone +33 450 488567 • Fax +33 450 562378 • sales.fr@bgb-analytik.com

 Germany
 BGB Analytik Vertrieb GmbH • Mühlestraße 1 • 79539 Lörrach • Phone +49 7621 5884270 • Fax +49 7621 5884289 • sales.de@bgb-analytik.com